1-15 Vertical Laminar Flow Clean Bench



Product Description

Vertical clean bench is a working table with the function of air purifying. It is mainly applied to manufacturing areas of precise products which require a specific clean environment. It suck in air through fan, pass through static pressure box and then pass through HEPA filter. The purified air can reach ISO 5 clean class to meet the environment requirement for production.

Configuration Option

- 1. Material: Powder coated steel, Polish SUS 201 /304/316; Mirror SUS 201/304/316
- 2. Supply Power: AC 1/3N 220, 380V/50, 60Hz
- 3. Door: without door; manual lifting door

Product Parameter

| Item | Vertical Laminar Flow Clean Bench | | | |
|-------------------------|---|-------------------|------------------|--|
| Model | YN-CZT-01 | YN-CZT-02 | YN-CZT-03 | |
| External size W×D×H(mm) | 1000×700×1850 | 1200×700×1850 | 1500×700×1850 | |
| Internal Size W×D×H(mm) | 900×650×600 | 1100×650×600 | 1400×650×600 | |
| HEPA Filter(mm) | 800×500×69×1 Pcs | 1000×500×69×1 Pcs | 1300×500×69×1 Pc | |
| HEPA Filter Efficiency | 99.95%@0.3µm | 99.95%@0.3µm | 99.95%@0.3µm | |
| G4 Pre Filter(mm) | 495x495x21x1 Pcs | 495x495x21x1 Pcs | 495×495×21×1 Pcs | |
| Noise | 52 ~ 62dB (A) | 52 ~ 62dB (A) | 52 ~ 62dB (A) | |
| Fan Pressure | 260pa | 260pa | 260pa | |
| Fan Power (W) | 200W×1 Pcs | 200W×1 Pcs | 200W×1 Pcs | |
| LED Lamp Power(W) | 12W×1 Pcs | 18W×1 Pcs | 30W×1 Pcs | |
| Air Velocity(m/s) | 0.45m/s±20% | | | |
| Clean Level | ISO 5 | | | |
| Supply Power | AC 1N 220V/50Hz | | | |
| Control System | 4.3"touch screen,3 stage regulation,light,sterilization | | | |

1-16 Horizontal Laminar Flow Clean Bench



Product Description

Horizontal clean bench is a working table with the function of air purifying. It is mainly applied to manufacturing areas of precise products which require a specific clean environment. It suck in air through fan,pass through static pressure box and then pass through HEPA filter. The purified air can reach ISO 5 clean class to meet the environment requirement for production.

Configuration Option

- 1. Material: Powder coated steel, Polish SUS 201 /304/316: Mirror SUS 201/304/316
- 2. Supply Power: AC 1/3N 220, 380V/50, 60Hz
- 3. Door: without door; manual lifting door

Product Parameter

| Item | Horizontal Laminar Flow Clean Bench | | | |
|-------------------------|---|-------------------|-------------------|--|
| Model | YN-SPT-01 | YN-SPT-02 | YN-SPT-03 | |
| External size W×D×H(mm) | 1000×850×1500 | 1200×850×1500 | 1500×850×1500 | |
| Internal Size W×D×H(mm) | 960×600×600 | 1160×600×600 | 1460×600×600 | |
| HEPA Filter(mm) | 905×585×69×1 Pcs | 1105×585×69×1 Pcs | 1405×585×69×1 Pcs | |
| HEPA Filter Efficiency | 99.95%@0.3µm | 99.95%@0.3µm | 99.95%@0.3µm | |
| G4 Pre Filter(mm) | 500×375×21×1 Pcs | 500×375×21×1 Pcs | 745×375×21×1 Pcs | |
| Noise | 52 ~ 62dB (A) | 52 ~ 62dB (A) | 52 ~ 62dB (A) | |
| Fan Pressure | 260pa | 260pa | 260pa | |
| Fan Power (W) | 200W×1 Pcs | 200W×1 Pcs | 200W×1 Pcs | |
| LED Lamp Power(W) | 12W×1 Pcs | 18W×1 Pcs | 30W×1 Pcs | |
| Air Velocity(m/s) | 0.45m/s±20% | | | |
| Clean Level | ISO 5 | | | |
| Supply Power | AC 1N 220V/50Hz | | | |
| Control System | 4.3"touch screen,3 stage regulation,light,sterilization | | | |

www.dgvnc.cor